

2000 M Street, NW 7th Floor Tel 202.261.1000
Washington, D.C. 20036-3307 Fax 202.887.0336

MANELLI DENISON & SELTER PLLC**FACSIMILE TRANSMISSION**

TO: Examiner Jean

FAX: 571 273 3937

OF: USPTO

FROM: William H. Bollman

PHONE: 202-261-1020

FAX: 202-887-0336

DATE: February 15, 2007

NUMBER OF PAGES: 2 3 (including cover)

MESSAGE: U.S. Application Re: 09/630,762

THIS MESSAGE MAY CONTAIN PRIVILEGED AND CONFIDENTIAL INFORMATION
INTENDED SOLELY FOR THE INDIVIDUALS OR ENTITIES TO WHICH IT IS
ADDRESSED. IF YOU ARE NOT THE ADDRESSEE OR THE EMPLOYEE OF THE
ADDRESSEE RESPONSIBLE FOR THE DELIVERY OF THIS MESSAGE, PLEASE NOTE
THAT ANY DISSEMINATION OR COPYING OF THIS MESSAGE OR DISCLOSURE OF ITS
CONTENTS IS STRICTLY PROHIBITED. IF YOU HAVE RECEIVED THIS MESSAGE IN
ERROR, PLEASE NOTIFY US BY PHONE FOR INSTRUCTIONS ON ITS RETURN OR
DISPOSAL.

THANK YOU.

U.S. Appl. No. 09/630,762 to Smith

Insert on page 1, line 2, the following:

This application claims priority from U.S. Provisional Application No. 60/199,367, filed April 25, 2000.

Amend paragraph on page 31, lines 14-22 as follows:

A wireless Internet gateway 100 in accordance with the principles of the present invention is particularly useful for wireless carriers and/or Internet service providers (ISPs). For instance, a wireless Internet gateway 100 can also be used within the Enterprise and ISP markets to provide a single point of entry for short message system (SMS) delivery to multiple wireless carriers. ~~This is detailed in a co-owned U.S. Appl. No. 60/_____, filed _____ by Richard Smith, and entitled "Web Gateway Multi Carrier Support", which in its entirety is explicitly incorporated herein by reference.~~

of the present invention. In these exemplary scenarios, an E-mail message is communicated.

Certain aspects of communications between mobile devices and the wireless Internet gateway are shown and described in co-owned
 5 U.S. Appl. No. 60/198,108, filed 4/18/00 by Richard A. Smith and Johanna Wilson, entitled "Short Messaging Service Center SMPP to HTTP Internet Communications", the entirety of which is expressly incorporated herein by reference.

Fig. 7A shows an exemplary message flow when a wireless
 10 Internet gateway 100 originates a short message requiring SME delivery acknowledgement and a response from the recipient, in accordance with the principles of the present invention.

In particular, as shown in Fig. 7A, a wireless Internet gateway 100 sends a message to a mobile wireless handset device, and
 15 requests two types of delivery feedback: (1) acknowledgement of when the user reads the message; and (2) a response code from the user.

The message is derived from an E-mail message received from the Internet to an address, e.g., "MIN@[gateway]". The wireless Internet gateway 100 supplies the sender's E-mail address so that it may
 20 be processed by the mobile wireless handset device.

Note that in the preferred embodiment, the wireless Internet gateway 100 will not request delivery feedback of any kind when submitting short messages for incoming E-mail.

In step 1 of Fig. 7A, the wireless Internet gateway generates
 25 a SUBMIT_SM message with key elements populated in the following way:

- service_type: page
- source_addr: [sender's E-mail address]
- destination_addr: handset's MIN
- 30 - registered_delivery_flag: 12 (bits 2&3 enabled)